

Planet eCam Auto Tracking Fixed Box Camera

Parameters	N/PLA/ETRACK/FIXED
Camera Parameter	
Sensor	1/2.8 inch high-quality 4K CMOS sensor
Effective Pixels	8.28 million, 16:9
Video Signals	SDI interface: 1080P@30fps/25fps; 720P@60fps/50fps/30fps/ 25fps; U3 interface: 1920X1080P30fps /25 fps; 1280X720P60 fps /50 fps /30 fps /25 fps; 960X540P30fps; 640X360P30 fps; 640X480P30 fps; 352X288P30 fps; 960X540P30 fps; 800X600P30 fps; compatible with USB2.0 output
View Angle	57.2°(D) /47°(H)/36°(V)
Focal Length	f=7.23mm
Iris	F2.4+ 5%
Digital Zoom	3X
Minimum Illumination	0.5Lux (F1.8, AGC ON)
DNR	2D & 3D DNR
White Balance	Auto/Manual/ One Push/Specified color temperature (2400K- 7100K, step size is 100)
Focus	Manual
Exposure	Fixed
Backlight	On/Off
Contrast	
SNR	>50dB
Input/Output Interface	
Video Output Interface	1 × SDI 1 × USB 1 × LAN: 10M/100M/1000M adaptive Ethernet port (POE Support)
Video Compression	H.264, H.265, MJPEG
Audio Input Interface	Dual audio channel 3.5mm linear input
Audio Compression	AAC, MP3, G.711A
Network Protocol	RTSP, RTMP, ONVIF, GB/T28181
Control Interface	RS232, RS485, LAN
Control Protocol	VISCA, Pelco-D, Pelco-P; support baud rate 115200 /38400/9600/4800/2400; support network VISCA control protocol
Power Interface	HEC3800 power socket (DC12V)

Other Parameter		
Working Voltage	Power Adapter	12V
	POE Power Supply	48V
Working Current	Power Adapter	0.42A(max)
	POE Power Supply	0.104A(max)

Power Consumption	5W(max)
Storage Temperature	-10°C - +60°C
Storage Humidity	20% - 95%
Working Temperature	-10°C - +50°C
Working Humidity	20%~80%
Dimension (WxHxW)	148.8mm×76mm×76mm
Weight	0.53kg
Application	Indoor
Accessory	User manual
Dimension (mm)	



